

RX SERIES

Single-phase

Three-phase


Ask for our FREE detailed CD-rom manual:
REF 107TA8608

Box S




250 x 200 x 320 mm

Box A



430 x 285 x 270 mm

Box B



500 x 340 x 360 mm

Box C



500 x 360 x 700 mm



1 year warranty
on all charger parts!

EXTENDED RANGE

General information RX

- Fully automatic, microprocessor-controlled battery charger.
- Compact and simple construction.
- LED control panel :
 - Battery connected – in charge
 - Final charge
 - Charge complete - Equalization
 - Emergency stop
 - Black-out of the mains
 - Ammeter 0 -100%
- Automatic equalization of the battery.
- Automatic start on battery connection, with 3 delays to avoid arcing between the connectors. Automatic shutdown on battery disconnection during the charge.
- Automatic saving of the charge parameters in case of black-out of the mains and automatic restart when the input is available.
- Input voltages single-phase 220 VAC or three-phase 380 VAC. Other input voltages available on request.
- Charge curve Wa (DIN41774).
- 1 year warranty (on spare parts).

RX SERIES

REF	Volt	Amp	Capacity range vs time of charge	Box	Weight	Input power
RX/ Single-phase / 220 VAC						
122TA8161	24 V	20 A	100-120 Ah	S	13 kg	0,70 kVA
122TA8162	24 V	25 A	125-150 Ah	S	14 kg	0,85 kVA
122TA8163	24 V	30 A	150-180 Ah	S	17 kg	1,00 kVA
122TA8164	24 V	40 A	200-240 Ah	A	19 kg	1,30 kVA
122TA8165	24 V	50 A	250-300 Ah	A	22 kg	1,70 kVA
122TA8166	24 V	60 A	300-360 Ah	A	24 kg	2,00 kVA
139TA2548	24 V	80 A	360-500 Ah	B	40 kg	2,80 kVA
122TA8167	48 V	60 A	300-360 Ah	B	43 kg	4,20 kVA
122TA8168	48 V	80 A	360-500 Ah	B	48 kg	5,60 kVA
138TA4138	48 V	100 A	500-599 Ah	B	47 kg	7,00 kVA
138TA4139	48 V	120 A	600-749 Ah	B	51 kg	8,40 kVA
RX/ Three-phase / 380 VAC						
122TA8169	24 V	60 A	300-360 Ah	B	37 kg	2,10 kVA
122TA8170	24 V	80 A	360-500 Ah	B	41 kg	2,80 kVA
122TA8171	24 V	100 A	500-600 Ah	B	44 kg	3,50 kVA
138TA4140	24 V	120 A	600-749 Ah	B	50 kg	4,20 kVA
138TA4141	24 V	140 A	750-899 Ah	C	52 kg	4,90 kVA
138TA4142	24 V	160 A	900-1024 Ah	C	56 kg	5,60 kVA
138TA4143	24 V	180 A	1025-1149 Ah	C	58 kg	6,30 kVA
138TA4144	24 V	200 A	1185-1299 Ah	C	65 kg	7,00 kVA
122TA8172	36 V	60 A	300-360 Ah	B	41 kg	3,10 kVA
122TA8173	36 V	80 A	360-500 Ah	B	45 kg	4,20 kVA
122TA8174	36 V	100 A	500-600 Ah	B	48 kg	5,20 kVA
138TA4145	36 V	120 A	600-749 Ah	B	50 kg	6,20 kVA
138TA4146	36 V	140 A	750-899 Ah	C	55 kg	7,30 kVA
138TA4147	36 V	160 A	900-1024 Ah	C	62 kg	8,30 kVA
138TA4148	36 V	180 A	1025-1149 Ah	C	68 kg	9,40 kVA
138TA4149	36 V	200 A	1185-1299 Ah	C	80 kg	10,40 kVA
122TA8175	40 V	50 A	250-300 Ah	B	40 kg	4,40 kVA
122TA8176	40 V	60 A	300-360 Ah	B	42 kg	5,30 kVA
122TA8177	40 V	80 A	360-500 Ah	B	48 kg	7,00 kVA
122TA8178	48 V	50 A	250-300 Ah	B	39 kg	2,80 kVA
122TA8179	48 V	60 A	300-360 Ah	B	43 kg	4,20 kVA
122TA8180	48 V	80 A	360-500 Ah	B	49 kg	5,60 kVA
122TA8181	48 V	100 A	500-600 Ah	B	53 kg	7,00 kVA
138TA4150	48 V	120 A	600-749 Ah	B	62 kg	8,40 kVA
138TA4151	48 V	140 A	750-899 Ah	C	70 kg	9,80 kVA
138TA4152	48 V	160 A	900-1024 Ah	C	79 kg	11,20 kVA
138TA4153	48 V	180 A	1025-1149 Ah	C	86 kg	12,60 kVA
138TA4154	48 V	200 A	1185-1299 Ah	C	94 kg	14,00 kVA
122TA8182	72 V	60 A	300-360 Ah	B	53 kg	6,30 kVA
122TA8183	72 V	80 A	360-500 Ah	B	55 kg	8,30 kVA
138TA4155	72 V	100 A	500-599 Ah	C	71 kg	10,50 kVA
138TA4156	72 V	120 A	600-749 Ah	C	83 kg	12,50 kVA
122TA8184	80 V	60 A	300-360 Ah	B	55 kg	6,90 kVA
138TA4157	80 V	80 A	360-500 Ah	B	65 kg	9,20 kVA
138TA4158	80 V	100 A	500-599 Ah	C	80 kg	11,50 kVA
138TA4159	80 V	120 A	600-749 Ah	C	87 kg	13,80 kVA
All parts available						

[Click here to see the complete Energic Plus catalogue](#)